



Levelfix LLD/RLD/DLD

Technical data

LEVELFiX

INSTRUMENTS



	LLD100GR	RLD100GR	DLD100GR
Working Range	50m (165ft)	150m (500ft)	300m (1000ft)
Reception window	80mm	127mm	
Display	LCD with backlit, LED indication, arrows - 3 channels		LCD with backlit, Digital reading (mm, inch), LED, arrows - 11 channels
Accuracy	Fine: 1mm (0.05 in) Coarse: 2mm (0.10 in)		High: 1mm (0.05 in) Normal: 2mm (0.10 in) Low: 5mm (0.20 in) Lowest: 10mm (0.50 in)
Suitable for	Line lasers, red and green	Rotary lasers, red and green (with visible beam)	Rotary lasers, red and green (all beams)
Mounting options		LS-BK100 Clamp (included) or magnets on top	
Battery		2x AA Alkaline IEC LR6	
Operating time		24 Hr	
Auto power off		After 30 minutes	
Size (L x W x H)	155 mm x 70 mm x 25 mm (6.1 in x 2.8 in x 1.0 in)		160 mm x 72 mm x 30 mm (6.3 in x 2.8 x 1.2)
Weight	0.26 kg (0.57 lb)		0.34 kg (0.75 lb)
Laser Safety		IP66	
Temperature			
Storage temperature		-20° C to 70° C (-4 °F to 140 °F)	
Operating temperature		-10° C to 50° C (14 °F to 122 °F)	